

{Portable}

CW Premium Series

Gasoline - Belt Drive

Coined the "Workhorse Series", the robust CW Premium Series is specially designed with premier 1/4-inch steel base plates-unlike any other unit on the market! This Series also offers a heavy-duty dual-cogged belt drive system and a hefty General Pump which comes with a 10-year limited warranty.



CW-3004-4MGH

Additional Features:

- ✓ Performance-proven engine with low-oil protection
- ✓ Belt drive triplex piston General pump with ceramic plungers
- ✓ Thermal relief valve
- ✓ Stainless-steel and brass unloader mounted on base plate
- ✓ Forged brass manifold (Nickel plated brass on CW-4004-3MV0)
- ✓ Two-piece belt guard with 1/4-turn release for quick access to belts
- ✓ Convenient hose wrap
- ✓ Dual rubber isolators
- ✓ Quick connect nozzles (0°, 15°, 25° and 40°)
- ✓ 50-foot x 3/8-inch non-marking hose with quick connects, swivel and bend restrictors
- ✓ Professional-grade insulated trigger gun with safety lock-off
- ✓ 36-inch lance with rubber grip (48-inch lance on 3500- & 4000-PSI models)



Specifications:

Model #	CW-2505-4MGH	CW-3004-4MGH	CW-3504-4MGH	CW-3504-4MGR
Pressure (psi)	2500	3000	3500	3500
Flow (gpm)	4.4	3.5	3.7	3.7
Engine	Honda OHV	Honda OHV	Honda OHV	Subaru OHV
Horsepower	13.0	13.0	13.0	13.5
Dim. (LxWxH)	45.5in.x28in.x26in.	45.5in.x28in.x26in.	46in.x28in.x30in.	46in.x28in.x30in.
Shipping weight	290 lbs.	290 lbs.	290 lbs.	290 lbs.
Net weight	216 lbs.	216 lbs.	216 lbs.	216 lbs.

Model #	CW-4003-3MGH	CW-4003-3MGR	CW-4004-3MV0*
Pressure (psi)	4000	4000	4000
Flow (gpm)	3.0	3.0	4.0
Engine	Honda OHV	Subaru OHV	Vanguard OHV
Horsepower	13.0	13.5	16.0
Dim. (LxWxH)	46in.x28in.x30in.	46in.x28in.x30in.	46in.x28in.x30in.
Shipping weight	290 lbs.	290 lbs.	330 lbs.
Net weight	216 lbs.	216 lbs.	256 lbs.

*Electric start (battery included).



CW-3504-4MGR

Options:

50-0161	High pressure detergent injection - High pressure water mixes with detergent to clean even the heaviest build-up
AW-8400-0021	Low pressure detergent injection - Allows the user to apply the recommended detergents
CX-0005	Insulated dual lance - Has both a high and low pressure tip that allows you to switch to the low pressure chemical injector without having to change tips
CX-0006	4000-PSI hose - Upgrades pressure hose to 4000-PSI rating
CX-0045	Electric start (battery included) - For easy starting
CX-0054, CX-0055	Roll cage - Designed for cold water pressure washers to protect equipment, comes with a lifting hook, 1-1/4-inch powder coated steel tubing
TX-1302-M	Puncture-proof tires - Tires are flat-free, maintenance-free and non-marking, 13-inch, white hub, two tires

Model #	50-0161	AW-8400-0021	CX-0005	CX-0006	CX-0045	CX-0054	CX-0055	TX-1302-M
CW-2505-4MGH	●	●	●	●	●	●		●
CW-3004-4MGH	●	●	●	●	●	●		●
CW-3504-4MGH	●	●	●	●	●	●		●
CW-3504-4MGR	●	●	●	●	●	●		●
CW-4003-3MGH	●	●	●	●	●	●		●
CW-4003-3MGR	●	●	●	●	●	●		●
CW-4004-3MV0	●	●	●	●			●	●

**270 Interstate Court
 Fredrick, MD 21704
 (301) 663-4683
 (800) 221-6905**