

CWC Series Gasoline - Belt Drive

This large-PSI model comes protected in a roll-cage design, offering up an abundance of pressure in a compact, user-friendly unit. The 8-hour run time capacity is especially useful for continuous operations typical in many industrial applications.



CWC-5004-1MGH

Removable fuel tank (11.5-gallon capacity) allows for 8-hour running time

Powder coated steel frame with 1 1/4-inch roll cage, handles and lifting hook

Pneumatic mag tires with tubes, locking tire brake and solid steel threaded axles

Low tone high mount muffler (3008-, 5005- & 6004-PSI models)

Additional Features:

- ✓ Performance-proven OHV engine with low-oil protection
- ✓ Electric start (battery included)
- ✓ Belt drive triplex piston General or AR pump with ceramic plungers
- ✓ Thermal relief valve
- ✓ Preset stainless-steel and brass unloader
- ✓ Forged brass manifold
- ✓ Safety relief valve
- ✓ Easy start valve (3000-PSI model)
- ✓ Water filter with clear sleeve for screen inspection (High capacity water filter on 3000-PSI model)
- ✓ Heavy-duty dual cogged belt drive system with cast iron pulleys
- ✓ Two-piece belt guard with 1/4-turn release for quick access to belts
- ✓ Hose wrap with gun/wand holder
- ✓ Quick connect nozzles (0°, 15°, 25° and 40°)
- ✓ 50-foot x 3/8-inch non-marking hose with quick connects, swivel and bend restrictors (1/2-inch diameter on 3000-PSI model)
- ✓ Professional-grade insulated trigger gun with safety lock-off
- ✓ 48-inch lance with rubber grip



Specifications:

Model #	CWC-3008-2MGH*	CWC-5004-1MGH	CWC-5004-2MGH*	CWC-5005-2MGH*	CWC-6004-2MGH*
Pressure (psi)	3000	5000	5000	5000	6000
Flow (gpm)	7.8	4.0	4.0	4.5	3.7
Engine	Honda OHV	Honda OHV	Honda OHV	Honda OHV	Honda OHV
Horsepower	24.0	20.0	20.0	24.0	24.0
Dim. (LxWxH)	43in.x27.75in.x36in.	43in.x27.75in.x36in.	43in.x27.75in.x36in.	43in.x27.75in.x36in.	43in.x27.75in.x36in.
Shipping weight	511 lbs.	501 lbs.	501 lbs.	511 lbs.	511 lbs.
Net weight	388 lbs.	378 lbs.	378 lbs.	388 lbs.	388 lbs.

* Models equipped with General pumps, all other models equipped with AR pumps.

Options:

- AW-0018-0374 Rotating nozzle - Increase your cleaning power and decrease your cleaning time
 AW-3005-0035 Sand injector - Remove coatings from steel and concrete surfaces
 TX-1304-M Puncture-proof tires - Tires are flat-free, maintenance-free and non-marking, 13-inch, white hub, four tires



ETL Listed:
 CWC-5004-1MGH
 CWC-5004-2MGH
 CWC-5005-2MGH

Model #	AW-0018-0374	AW-3005-0035	TX-1304-M
All Models			●
CWC-5004		●	●
CWC-6004-2MGH	●	●	●

270 Interstate Court
 Fredrick, MD 21704
 (301) 663-4683
 (800) 221-6905