

Cold Water Pressure Washers - CWE Series

Stationary Wall Mount - Electric - Belt Drive

This stainless-steel pressure washer offers a superior package design and quiet operating system.

McHenry

PRESSURE CLEANING SYSTEMS

301-663-4683 or 800-221-6905

SALES • SERVICE • RENTALS

www.mchenrypcs.com



CWE-2004

Belt drive triplex piston General pump with ceramic plungers accepts incoming water up to 175°

Pump

- Stainless-steel and brass unloader
- Forged brass manifold
- Thermal relief valve
- In-line water strainer
- Quick connect low pressure detergent injection
- Bypass system

Motor

- Open drip-proof motor (1000 & 3000-PSI models)
- Totally enclosed fan-cooled electric motor with manual thermal overload protection (2000-PSI models)
- 4-foot electrical cord with ground fault circuit interrupter (NEMA 5-20P, 20-amp plug on 1000-PSI model)

Frame

- Stainless-steel base and frame
- Removable panel for pump access
- Easy-to-access cabinet design
- Four rubber isolators

Components

- Dual cogged belt drive system for increased belt life
- Conveniently located on/off switch
- Time delay shutdown will shut unit off automatically when trigger gun is released and timer reaches setting

Unit Includes

- Quick connect nozzles (0°, 15°, 25° and 40°)
- 50-foot x 3/8-inch pressure hose with quick connects, swivel and bend restrictors
- Professional-grade insulated trigger gun with safety lock-off
- Adjustable pressure insulated dual lance

Model Number	PSI	GPM	HP/Motor	Plug Type	Dimensions (LxWxH)	Ship Wt.	Net Wt.
CW-1003-SME1	1000	2.5	2.0 HP, 120V, 1Ø, 18.8A	NEMA 5-20P	29.5in.x20.5in.x15in.	222 lbs.	172 lbs.
CW-2004-SME1	2000	3.9	6.0 HP, 230V, 1Ø, 24.1A	NEMA 6-30P	29.5in.x20.5in.x15in.	272 lbs.	214 lbs.
CW-3004-SME3	3000	3.5	8.0 HP, 230V, 3Ø, 20.0A	NEMA L15-30P	29.5in.x20.5in.x15in.	292 lbs.	234 lbs.